



Geschweißte und nahtlose Edelstahlbogen
nach EN10253-4 BA3
Welded an seamless stainless steel elbows
acc. to EN 10253-4 BA3

| | | | | |
|------|--------|--------|--------|--------|
| AISI | 304 L | 316 L | 316 Ti | 321 |
| DIN | 1.4307 | 1.4404 | 1.4571 | 1.4541 |

| Außendurchmesser (mm) | Radius (mm) | | Wanddicke (mm) | | | | | | | | | | | |
|-----------------------|-----------------------|-------------|---------------------|-----|-----|---|-----|-----|---------|-----|-----|---|-----|---|
| | Outside diameter (mm) | radius (mm) | wall thickness (mm) | | | | | | | | | | | |
| | | | | 1,5 | 1,6 | 2 | 2,3 | 2,6 | 2,9/3,0 | 3,2 | 3,6 | 4 | 4,5 | 5 |
| 12 | 20 | | | x | | x | | | | | | | | |
| 13,5 | 20 | | | | x | | x | | | | | | | |
| 15 | 20 | 27,5 | | x | | x | | | | | | | | |
| 16 | 20 | 27,5 | | x | | x | | | | | | | | |
| 17,2 | 20 | 25 | 27,5 | | x | x | x | | | | | | | |
| 18 | 20 | 22,5 | 25 | x | | x | | | | | | | | |
| 20 | 25 | 30 | | x | | x | | | | | | | | |
| 21,3 | 27 | 28 | | | x | x | | x | | x | | | | |
| 23 | 35 | | | x | | | | | | | | | | |
| 25 | 27,5 | 37 | | x | | x | | | | | | | | |
| 26,9 | 28 | 29 | | | x | x | | x | | x | | | | |
| 28 | 32,5 | 40 | | x | | x | | | | | | | | |
| 30 | 33,5 | 45 | | x | | x | | | | | | | | |
| 33 | 50 | | | x | | | | | | | | | | |
| 33,7 | 38 | | | | x | x | | x | | | x | | | |
| 34 | 38 | | | x | | x | | | | | | | | |
| 35 | 45 | 52,5 | | x | | x | | | | | | | | |
| 38 | 45 | 55 | | x | | x | | | | | | | | |
| 40 | 45 | 60 | | x | | x | | | | | | | | |
| 42,4 | 47 | 48 | | | x | x | | x | x | x | x | | | |
| 43 | 47,5 | 65 | | x | | | | | | | | | | |
| 44,5 | 51 | 65 | | | | x | | x | | | | | | |
| 48,3 | 57 | | | | x | x | | x | x | x | x | x | | |
| 50 | 71 | | | x | | x | | | | | | | | |
| 50,8 | 76 | | | x | | x | | | | | | | | |

| Außendurchmesser (mm) | Radius (mm) | | Wanddicke (mm) | | | | | | | | | | |
|-----------------------|-------------|------|---------------------|-----|---|-----|-----|---------|-----|-----|---|-----|---|
| Outside diameter (mm) | radius (mm) | | wall thickness (mm) | | | | | | | | | | |
| | | | 1,5 | 1,6 | 2 | 2,3 | 2,6 | 2,9/3,0 | 3,2 | 3,6 | 4 | 4,5 | 5 |
| 52 | 70 | 78 | x | | x | | | | | | | | |
| 53 | 72,5 | 80 | x | | | | | | | | | | |
| 54 | 70 | 80 | x | | x | | | | | | | | |
| 57 | 75 | 85,5 | x | | | | | | | | | | |
| 60,3 | 76 | | x | x | x | | x | x | x | x | x | | |
| 63,5 | 95 | | x | x | x | | | | | | | | |
| 70 | 92 | | x | | x | | | | | | | | |
| 73 | 110 | | x | | | | | | | | | | |
| 76 | 115 | | x | | | | | | | | | | |
| 76,1 | 95 | | x | x | x | x | x | x | x | x | x | x | x |
| 84 | 105 | 120 | | | x | | | | | | | | |
| 88,9 | 114 | | x | x | x | x | x | x | x | x | x | x | x |
| 101,6 | 133,5 | | x | | x | | | | | | | | |
| 104 | 155 | | | | x | | | | | | | | |
| 108 | 142,5 | | | | x | | | | | | | | |
| 114,3 | 152 | | | | x | x | x | x | | x | x | x | x |
| 129 | 190 | | | | x | | | | | | | | |
| 133 | 181 | | | | | | | x | | | | | |
| 139,7 | 190 | | | | x | | x | x | | | x | | |
| 154 | 225 | | | | x | | | | | | | | |
| 156 | 225 | | | | | | | x | | | | | |
| 159 | 216 | | | | | | | x | | | x | | |
| 168,3 | 229 | | | | x | | x | x | | | x | | |



Geschweißte und nahtlose Edelstahlbogen
nach EN10253-4 BA2
Welded an seamless stainless steel elbows
acc. to EN 10253-4 BA2

| | | | | |
|------|--------|--------|--------|--------|
| AISI | 304 L | 316 L | 316 Ti | 321 |
| DIN | 1.4307 | 1.4404 | 1.4571 | 1.4541 |

| Außendurchmesser (mm) | Radius (mm) | Wanddicke (mm) | | | |
|-----------------------|-------------|---------------------|-----|---|-----|
| Outside diameter (mm) | radius (mm) | wall thickness (mm) | | | |
| | | 2 | 2,6 | 3 | 3,2 |
| 21,3 | 17,5 | x | | | |
| 26,9 | 25 | x | x | | |
| 33,7 | 25 | x | x | | |
| 42,4 | 32 | x | x | | |
| 48,3 | 38 | x | x | | |
| 60,3 | 51 | x | x | | |
| 76,1 | 63 | x | x | | |
| 88,9 | 76 | x | | | x |
| 104 | 100 | x | | | |
| 114,3 | 102 | x | x | | |
| 139,7 | 125 | | x | | |
| 168,3 | 152 | | | x | |



Geschweißte und nahtlose Edelstahlbogen
nach EN10253-4 BA5
Welded an seamless stainless steel elbows
acc. to EN 10253-4 BA5

| | | | | |
|------|--------|--------|--------|--------|
| AISI | 304 L | 316 L | 316 Ti | 321 |
| DIN | 1.4307 | 1.4404 | 1.4571 | 1.4541 |

| Außendurchmesser (mm) | Radius (mm) | Wanddicke (mm) | | | | |
|-----------------------|-------------|---------------------|-----|-----|---|-----|
| | | wall thickness (mm) | | | | |
| Outside diameter (mm) | radius (mm) | 2 | 2,6 | 2,9 | 3 | 3,2 |
| 21,3 | 42,4 | x | x | | | |
| 26,9 | 57,5 | x | x | | | |
| 33,7 | 72,5 | x | x | | | x |
| 42,4 | 92,5 | x | x | | | x |
| 48,3 | 107,5 | x | x | | | x |
| 60,3 | 135 | x | x | x | | |
| 76,1 | 175 | x | x | | | |
| 88,9 | 205 | x | x | | | x |
| 104 | 250 | x | | | | |
| 114,3 | 270 | x | x | | | |
| 129 | 312,5 | x | | | | |
| 139,7 | 330 | x | x | | | |
| 168,3 | 390 | | x | | x | |